

SÉRIE VA - VAV

TLAK 10 BAR



Pracovní teplota	Vnější povrch (barva)	Přyzová membrána
od -10 °C do +100 °C od -10 °C do +70 °C (2 000 - 10 000)	RAL 5010 RAL 3000 (VAV 750 - 10 000)	EPDM BUTYL (VAV 2000 - 10 000)

TYP	Výška (mm)	Průměr (mm)	Max. prac. tlak (bar)	Standardní plnicí tlak	Připojení
VA 5	304	160	10	1,5	3/4"
VA 8	316	200		1,5	3/4"
VA 12	295	280		1,5	3/4"
VA 18	423	280		1,5	3/4"
VA 24	489	280		1,5	1"
VA 35	450	365		1,5	1"
VAV 50	656	365		1,5	1"
VAV 60	783	365		1,5	1"
VAV 80	810	410		1,5	1"
VAV 100	849	495		1,5	1"
VAV 150	975	550		1,5	1"
VAV 200	1085	600		2	1 1/4"
VAV 300	1240	650		2	1 1/4"
VAV 500	1490	750		2	1 1/4"
VAV 750	1820	800		4	2"
VAV 1000	2160	800		4	2"
VAV 1500	2360	960		4	2"
VAV 2000	2555	1100		4	2"
VAV 3000	2790	1200		4	DN65
VAV 4000	3200	1450		4	DN80
VAV 5000	3645	1450	4	DN80	
VAV 10 000	5350	1500	4	-	